

**Features:**

- \* 4 stage charging
- \* Charger for lead-acid batteries
- \* Energy saving mode
- \* Front panel indicator for operation status
- \* Thermostatically controlled cooling fan
- \* Protections: Over voltage / Over temp. / Output short
- Input polarity reverse
- \* Approvals: EMC/LVD/e13/CE/SGS/ROHS/ISO 9001



Made in Taiwan

**SPECIFICATION**

Automatic Battery Charger	AD-1548
INPUT RANGE (volt)	230 AC +/- 10%
INPUT FREQUENCY	50~60 Hz
INPUT SOCKET	IEC plug
OUTPUT VOLTAGE(volt)	48 DC
Max. OUTPUT POWER	850W – 15A
MULTI-RATE CHARGING FUNCTION	Select by Slide Switch
4 STAGE CHARGING	Soft Start> Bulk> Absorp> Maint
RECOMMENDED BATTERY CAPACITY	45Ah~300Ah
OVER VOLT PROTECTION	Lower Output Current
SHORT CIRCUIT PROTECTION	Yes (by fuse)
OVER HEAT PROTECTION	Lower Output Current
REVERSE POLARITY PROTECTION	Yes (by fuse)
OPERATING TEMPERATURE RANGE(C)	-10 ~ +50
DIMENSION (L*W*H)	325*198*83mm
NET WEIGHT	3.3 Kg